



SPECIFICATIONS

Input Voltage.....	208-240VAC, 3-Phase
Kilowatt Rating.....	18.0KW
Maximum Amperage.....	44 AMPS
Overcurrent Protection Size.....	60 AMPS
Water Inlet.....	3/8" Compression
Steam Outlet.....	1" NPT
Safety Valve.....	3/4" NPT
Electrical Connection.....	Hardwired
Room Size (Cubic Feet).....	<1000

PowerPak Series III Commercial Steam Generator

PowerPak Series III Standard Equipment:

- System components come packaged together for convenient ordering
- Pre-installed 3/4" NPT Pop Safety Valve
- Fully programmable digital control system
- 7-day programmability: Specific to both time and temperature and optimized for day-to-day individual settings
- Microtouch Remote start controller
- PowerFlush inner tank cleaning system: automated pressurized decalcification system helps eliminate sediment build-up
- Stainless steel split-tank design adds longevity by separating the heating function from water feed function
- Constant steam at a constant rate: no irritating steam lags or bursts
- Superior heating elements: a level of corrosion protection far superior to copper, brass, or stainless
- 18-month parts and labor in-field warranty
- 1" NPT Steam Outlet
- Can be plumbed 50 ft. from the shower without upsizing the generator
- Stainless steel/Brass wetted components
- Powder Coated Steel Enclosure
- Temperature sensor with 50 ft. lead wires included

Installation Notes:

Generator must be installed by a licensed electrician.

Install this generator according to the installation guide supplied. Follow all local plumbing and electrical codes. Unit must be accessible for service and maintenance. Generator is factory sized: L x W x H = Steam Room Cubic Feet = <1000 Cu. Ft. Choose the appropriate generator.

Product Specification Basics:

The steam generator unit dimensions are approximately 19"L x 18-1/8"W x 32"H in dimension. The generator is made from powder coated steel / stainless steel and includes: PowerFlush, Split Tank design, and Master controller mounted on generator unit.

Shipping Information:

Weight.....120 lbs.
Length.....19 in.
Width.....18-1/8" in.
Height.....32 in.

For any further assistance please contact ThermaSol at
800.776.0711 or sales@thermasol.com

