



Round Styling

SPECIFICATIONS – MicroTouch Control

Construction.....	6061 Billet Aluminum
Display.....	16 LED Temperature Display
Interface.....	3 Capacitive Touch Buttons
Communication.....	ThermaSol CAN Bus
Supply Voltage.....	5V DC

Basic Functions:

- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

Installation Notes:

The control should be installed 60" inches from the floor of the shower, inside the shower only, and away from the steam head.

Finish Chart:

Select desired finish and replace XXX with code.

PC = Polished Chrome	PN = Polished Nickel
SC = Satin Chrome	SN = Satin Nickel
PB = Polished Brass	BN = Black Nickel
SB = Satin Brass	AN = Antique Nickel
AB = Antique Brass	PG = Polished Gold
COP = Polished Copper	ORB = Oil Rubbed Bronze
ACOP = Antique Copper	WHT = White
MB = Matte Black	

Product Specification:

The user interface control shall be 2.9" Dia x .63" in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

Shipping Information:

Weight..... 4 lbs.
Length.....12 in.
Width.....12 in.
Height.....6 in.

For any further assistance please contact
ThermaSol at 800.776.0711 or
sales@thermasol.com

