



SeeSnake® rM200 Camera Reel Series with TruSense®



The new RIDGID® SeeSnake® rM200 Camera Reel Series now features TruSense® technology for superior image clarity and camera functionality. Already known for its built-in versatility and portability, the rM200 series, now also has enhanced transportation and storage features. The interchangeable D2 Series Drums (D2A & D2B) provide various combinations of cable stiffness and spring flexibility to tackle any inspection job.

- **Enhanced camera functionality** – TruSense technology with High Dynamic Range (HDR) sensor and TiltSense™ inclinometer give crisp, always upright images and feedback on camera angle in-pipe
- **Interchangeability** – Easily interchangeable D2 drums for on-the-job flexibility and compatible with all SeeSnake monitors
- **Pushability** – Drums feature different push cable lengths, diameters, stiffness and springs for customized jobs
- **Portability** – Multi-functional pull handle and smooth wheels for easy transport and positioning
- **Increased storage** – New taller stow bins with increased internal capacity to store



rM200A Reel
Catalog No. 63658



rM200B Reel
Catalog No. 63663

SPECIFICATIONS

	rM200A	rM200B
• Length.....	21.0" (535 mm)	21.0" (535 mm)
• Width.....	13.6" (345 mm)	13.6" (345 mm)
• Height.....	24" (610 mm)	24" (610 mm)
• Drum Diameter.....	17" (432 mm)	17" (432 mm)
• Camera		
Diameter.....	1" (25 mm)	1" (25 mm)
Type.....	Self-leveling w/TruSense	Self-leveling w/TruSense
Resolution.....	640 x 480	640 x 480
• Spring Assembly		
Type.....	Single	Dual Nested
Length	12.4" (316 mm)	17.1" (435 mm)
• Line Capacity	1.5" – 8" (38 mm – 203 mm)	2" – 8" (51 mm – 203 mm)
• Push Cable		
Length	200' (61 m)	165' (50 m)
Diameter.....	0.3" (7.5 mm)	0.35" (8.9 mm)
Minimum Bend Radius.....	2.8" (70 mm)	3.5" (89 mm)
• Sonde.....	512 Hz, Flexmitter®	512 Hz, Flexmitter®

ORDER INFORMATION

CATALOG NO.	MODEL NO.	DESCRIPTION	WEIGHT (lb.) (kg)	
63658	rM200A	Reel, SeeSnake rM200A w/D2A Drum, TruSense	37.0	16.7
63663	rM200B	Reel, SeeSnake rM200B w/D2B Drum, TruSense	40.2	18.2
70758	D2A	Drum, rM200 D2A, TruSense	16.3	7.4
70763	D2B	Drum, rM200 D2B, TruSense	19.2	8.7



rM200 D2A Drum
Catalog No. 70758



rM200 D2B Drum
Catalog No. 70763



Scan for more
information on HQx Live

RIDGID.COM/seesnake